

CRS Precision electronic Co., LTD		Control NO	E1102
		Issued BY	ED
		Date Issued	2017/01/20
Document Name	SPEC-SA1271H-XXXXX	Date Revised	2021/11/19
		Revised Edition	A2

-INDEX-

1. SCOPE
- 2 APPLICABLE DOCUMENTS
- 3 REQUIREMENTS
- 4 PERFORMANCE
- 5 INFRARED REFLOW CONDITION
- 6 PRODUCT QUALIFICATION AND TEST SEQUENCE
- 7 PRINTED CIRCUIT BOARD SPECIFICATION

Approval By	Check By	Originator By
Shenzhijin	Leo_he	Yuxiaofang

CRS Precision electronic Co., LTD		Control NO	EI102
		Issued BY	ED
		Date Issued	2017/01/20
Document Name	SPEC-SA1271H-XXXXX	Date Revised	2021/11/19
		Revised Edition	A2

1 SCOPE

This specification covers performance, tests and quality requirements for **1.27/0.8 mm PITCH SAS CONN.**

2 APPLICABLE DOCUMENTS

EIA-364 ELECTRONICS INDUSTRIES ASSOCIATION

3 REQUIREMENTS

3.1 Design and Construction

Product shall be of design, construction and physical dimensions specified on applicable product drawing.

3.2 Materials and Finish

3.2.1 Contact: High performance copper alloy (**Phosphor Bronze**)

3.2.2 Finish :The finish for applicable components shall be as specified herein or equivalent.

3.2.3 Housing: **Thermoplastic, high temp. UL94V-0**

3.3 Ratings

3.3.1 Voltage: **30 Volts AC**

3.3.2 Current: **1.5 Amperes**

3.3.3 Operating Temperature: **0°C to +55°C**

Non-Operating: **-40°C to +85°C**

CRS Precision electronic Co., LTD		Control NO	E1102
		Issued BY	ED
Document Name	SPEC-SA1271H-XXXXX	Date Issued	2017/01/20
		Date Revised	2021/11/19
		Revised Edition	A2

4 Performance

4.1. Test Requirements and Procedures Summary

Item	Requirement	Standard
Examination of Product	Product shall meet requirements of applicable product drawing and specification.	Visual, dimensional and functional per applicable quality inspection plan.
ELECTRICAL		
Low-signal Level Contact Resistance	30 m Ω Max.initial 15 m Ω Max.change allowed.	Mate connectors, measure by dry circuit, 20mV Max., 100mA Max.(When manually operated,mating speed should be
Insulation Resistance	1000 MΩ Min.	Unmated connectors, apply 500 V DC between adjacent terminals. (EIA-364-21)
Dielectric Withstanding Voltage	500 VAC Min. at sea level for 1 minute. No discharge, flashover or breakdown. Current leakage: 0.5 mA max	Test between adjacent contacts of unmated connectors. (EIA-364-20)
Temperature Rise	30℃ Max.Change allowed	1. Mate connector,measure the temperature rise at rated current after.1.5A minimum Power contact. 2. The temperature rise above ambient shall not exceed 85 ℃. The ambient condition is still air at 25℃ 3. Wire power pins P1,P2, P8 and P9 in parallel for power 4. Wire ground pins P4,P5, P6,P10 and P12 in parallel for return 5. Supply 6A total DC current to the power pins in parallel,returning from the parallel ground pins(P4,P5,P6,P10 and P12)

CRS Precision electronic Co., LTD		Control NO	E1102
		Issued BY	ED
Document Name	SPEC-SA1271H-XXXXX	Date Issued	2017/01/20
		Date Revised	2021/11/19
		Revised Edition	A2

MECHANICAL

Item	Requirement	Standard
Connector Insertion Force	35N Max.(3.57 kg/f)	Operation speed: 25 mm/min. . (EIA-364-13)
Connector Extraction Force	5N Min. (0.5 kg/f) [At Initial and after Durability]	Operation speed: 25 mm/min. . (EIA-364-13)
Contact Retention Force	2.5N Min. (0.26 kg/f)	Operation speed: 5 mm/min. . (EIA-364-13)
Compliant Pin Insertion Force onto PCB(Per Pin)	50N Max.(5.1 kg/f)	Insert pin into application PCB hole at a maximum rate of 5 mm per minute.
Compliant Pin Retention Force onto PCB(Per Pin)	5N Min.(0.5 kg/f)	Apply axial pull out force on pin in PCB at a rate of 5 mm per minute.
Durability	500 cycles.	The sample should be mounted in the tester and fully mated and unmated the number of cycles specified at the rate of 200 cycles per hour . (EIA-364-09)
Vibration	1 μs Max.	The electrical load condition shall be 100 mA maximum for all contacts. Subject to a simple harmonic motion having amplitude of 0.76mm (1.52mm maximum total excursion) in frequency between the limits of 10 and 55 Hz . The entire frequency range, from 10 to 55 Hz and return to 10 Hz , shall be traversed in approximately 1 minute. This motion shall be applied for 2 hours in each of three mutually perpendicular directions. (EIA-364-28 Condition I)
Shock (Mechanical)	1 μs Max.	Subject mated connectors to 30 G's (peak value) half-sine shock pulses of 11 milliseconds duration. Three shocks in each direction shall be applied along the three mutually perpendicular axes of the test

CRS Precision electronic Co., LTD		Control NO	E1102
		Issued BY	ED
Document Name	SPEC-SA1271H-XXXXX	Date Issued	2017/01/20
		Date Revised	2021/11/19
		Revised Edition	A2

		specimen (18 shocks). The electrical load condition shall be 100mA maximum for all contacts. (EIA-364-27, test condition A)
--	--	---

ENVIRONMENTAL


Item	Requirement	Standard
Thermal Shock	See Product Qualification and Test Sequence Group 1	Mate module and subject to follow condition for 10 cycles. 1 cycles: -55°C , 30 minutes +85°C , 30 minutes (EIA-364-32, test condition A)
Temperature life	See Product Qualification and Test Sequence Group 2	Subject mated connectors to temperature life at 85°C for 500 hours. Measure Signal. (EIA-364-17, Test condition A)
Salt Spray	See Product Qualification and Test Sequence Group 3	Subject mated/unmated connectors to 5% salt-solution concentration, 35 °C for 48 hours . (EIA-364-26, Test condition B)
Humidity	See Product Qualification and Test Sequence Group 4	Mated Connector . 40°C , 90~95%RH , for 96 hours Reefer to Method II. (EIA-364-31, Test condition A)
Solder ability	Solder able area shall have minimum of 95% solder coverage.	Subject the test area of contacts into the flux for 5-10 sec. And then into solder bath, Temperature at 230 ±5 °C , for 10±1 sec using Type R flux. (EIA-364-52)
Resistance to Reflow Soldering Heat	See Product Qualification and Test Sequence Group 8 (Lead Free)	Pre Heat : 150°C~180°C, 60~90sec. Heat : 230°C Min., 40sec Min. Peak Temp. : 260°C Max, 10sec Max.

Note. Flowing Mixed Gas shall be conduct by customer request.

CRS Precision electronic Co., LTD		Control NO	E1102
		Issued BY	ED
		Date Issued	2017/01/20
Document Name	SPEC-SA1271H-XXXXX	Date Revised	2021/11/19
		Revised Edition	A2

5 INFRARED REFLOW CONDITION

5.1. Lead-free Process :



CRS Precision electronic Co., LTD		Control NO	EI102
		Issued BY	ED
Document Name	SPEC-SA1271H-XXXXX	Date Issued	2017/01/20
		Date Revised	2021/11/19
		Revised Edition	A2

6 PRODUCT QUALIFICATION AND TEST SEQUENCE

Test or Examination	Test Group									
	1	2	3	4	5	6	7	8	9	10
	Test Sequence									
Examination of Product	1、3	1、9	1、6	1、7	1、6	1、4	1、4	1、3		
Low-signal Level Contact Resistance		3、8	2、5	2、10	2、9		2、5			
Insulation Resistance				3、9	3、8					
Dielectric Withstanding Voltage				4、8	4、7					
Temperature Rise	2									
Connector Insertion Forces		2、7								
Connector Extraction Forces		4、6								
Contact Retention Force										1
Compliant Pin Insertion Force onto PCB						2				
Compliant Pin Retention Force onto PCB						3				
Durability		5								
Vibration			3							
Shock (Mechanical)			4							
Thermal Shock				5						
Temperature life					5					
Salt Spray							3			
Humidity				6						
Solder ability									1	
Resistance to Hand Soldering Heat								2		
Sample Size	2	4	4	4	4	4	4	4	2	4

CRS Precision electronic Co., LTD		Control NO	E1102
		Issued BY	ED
		Date Issued	2017/01/20
Document Name	SPEC-SA1271H-XXXXX	Date Revised	2021/11/19
		Revised Edition	A2

7 PRINTED CIRCUIT BOARD SPECIFICATION

Recommended Backplane PCB Thickness: 2.67~3.175mm minimum

